

NTE117 General Purpose Silicon Rectifier

Features:

- Cylindrical Design with Axial Leads for Simple Handling and Installation
- High Maximum Forward Current Rating: 750mA @ $T_A = +75^\circ\text{C}$
- Maximum Ambient Operating Temperature: $+175^\circ\text{C}$

Absolute Maximum Ratings:

| | |
|------------------------------------------------------------|-------------------------------------|
| DC Blocking Voltage, V_R | 600V |
| Forward Current ($T_A = +75^\circ\text{C}$), I_F | 750mA |
| Surge Current (50Hz), I_{Surge} | 45A |
| Operating Junction Temperature Range, T_J | -65° to $+175^\circ\text{C}$ |
| Storage Temperature Range, T_{stg} | -65° to $+175^\circ\text{C}$ |

Electrical Characteristics:

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-------------------------|--------|--------------------------------------------------|-----|-----|-----|------|
| Maximum Forward Voltage | V_F | $I_F = 500\text{mA}$, $T_A = +25^\circ\text{C}$ | - | - | 1.2 | V |
| Maximum Reverse Current | I_R | $V_R = 600\text{V}$, $T_J = +150^\circ\text{C}$ | - | - | 0.4 | mA |

